

# MegaPixel 56E

PoE Powered IR Illuminator



## MegaPixel PoE Powered Infrared

Simple PoE installation, just connect the lights CAT5e/CAT6 cable to a PoE++ midspan. Choose from six range/angle options to match the light to the camera's field of view. MegaPixel IR Illuminators are outdoor IP67 rated, rugged and vandal resistant.

## Easy Integration and Control

Seamless and precise control via Input/Output ports. Sync with camera, sensors or other system devices with I/O ports. For easy integration, a built-in photocell switches the IR ON/OFF based on lighting conditions.


## Lifetime Warranty - Made in the USA

AXTON Lights are covered by a lifetime warranty with advanced replacement.

## FEATURES

- Wavelength - 850nm Infrared
- Outdoor IP67 Rated
- Energy Efficient - 56 Watts
- Advanced LED Technology
- I/O Port Sync with Sensors, Devices
- Automatic Day/Night Sensor
- Lifetime Warranty, Made in the USA


## RANGE



Angle: <b>150°</b> Range: 185ft / 56m HFOV : 357ft / 108m	Angle: <b>90°</b> Range: 270ft / 82m HFOV : 347ft / 105m	Angle: <b>60° x 30°</b> Range: 420ft / 128m HFOV : 420ft / 128m	Angle: <b>30°</b> Range: 600ft / 182m HFOV : 310ft / 94m	Angle: <b>20° x 10°</b> Range: 800ft / 243m HFOV : 250ft / 76m	Angle: <b>10°</b> Range: 1200ft / 365m HFOV : 209ft / 63m
---	--	---	--	--	---

## SPECIFICATIONS

Wavelength	850nm Infrared
Input Voltage	PoE++
Angle/Range Options:	150°, 90°, 60°x30°, 30°, 20°x10° or 10°
Power Consumption	56 Watts
Operating Temp.	-58° to 140°F / -50° to 60°C
Dimensions	6.25" x 3.5" x 9.25" / 159 x 89 x 235mm
Weight	5.5 lbs / 2.5kg
Environmental	Outdoor IP67 Rated
Mounting	Pan/Tilt U Bracket Included



UNIVERSAL SOLUTIONS



801 Robinson Drive, Suite #500, North Salt Lake, UT 84054  
Tel: 801/519-0500 • Email: sales@axtontech.com • Website: axtontech.com

